

## Product Description

Product Name:	steel toe cap suede leather safety shoes for work
Item No:	SJ0200
Upper and Sole:	Upper: Genuine cow suede leather Sole: PU & Rubber (there is no pungent smell)
Toe:	1. Steel toe cap (or composite toe cap) to be impact resistant 200 joules.
	2. non is also provided.
Midsole :	1. Steel plate (or non-metallic anti-penetration mid sole) to be puncture resistant 1100 newton. 2. Non is also provided
Weight:	1.1 kgs/pr
Collar:	Genuine cow suede leather
Tongue:	Genuine cow suede leather
Lining:	Black air & dry mesh fabric (Your feet will be kept dry and comfortable)
Sockliner:	Moulded EVA or HI-POLY or PU (Greatly reduce your pain & fatigue from daily work)
Construction:	Injection
Height:	Low ankle
Size:	37-47 (3-13)
Standard:	CE EN ISO 20345 SBP SRC or others as your requirements
Guarantee:	6 months
Package:	Color inner box packing, 10 pairs in a carton.
Carton Size	58.5 x 40 x 32.5 cm
Load quantity of Container:	3300pairs /1x20' container 6600pairs /1x40' container

## Product Pictures



## ***Company Information***



Intertek																			
EC Type Examination Certificate																			
<b>CE</b>	<p><b>Issued to:</b> RUANG KONGSIKUN 59188-001 LTD SUNGU INDUSTRIAL ZONE, XINCHENG TOWN, RUANG DUTY, JIANGSU PROVINCE, CHINA</p> <p><b>Authorised Representative:</b> HANSEN STAR SAFETY PRODUCTS APAC (S) LTD 1-01 Village Square Tower, Jemena Centre, North Harbour City, Hong Kong</p> <p><b>Date of Issue:</b> 11 January 2018</p> <p><b>Expiry Date:</b> 11 February 2020</p> <p><b>Certificate No.:</b> L20170000047 (Extension of certificate L20170004196)</p> <p><b>Product Reference(s):</b> Safety Group: 4800V - 100A/2 4800V - 100A/4 4800V - 100A/6 4800V - 100A/8 4800V - 100A/10 4800V - 100A/12</p> <p><b>Description:</b>  <table border="0"> <tr> <td>Construction:</td> <td>Injection</td> </tr> <tr> <td>Terminal:</td> <td>Open terminal</td> </tr> <tr> <td>Material:</td> <td>Open cable</td> </tr> <tr> <td>Core:</td> <td>2000</td> </tr> <tr> <td>Size:</td> <td>4000 (Height)</td> </tr> <tr> <td>Mount:</td> <td>ACB</td> </tr> <tr> <td>Test frequency:</td> <td>See technical file</td> </tr> <tr> <td>Test range:</td> <td>25-40</td> </tr> <tr> <td>Country:</td> <td>4800V - 100A</td> </tr> </table> </p> <p><b>Signature:</b> <i>C.M.</i> <b>Date:</b> 11/01/2018</p> <p><b>Signature:</b> <i>[Signature]</i> <b>Date:</b> 11/01/2018</p> <p><b>Signature:</b> <i>[Signature]</i> <b>Date:</b> 11/01/2018</p> <p><b>Signature:</b> <i>[Signature]</i> <b>Date:</b> 11/01/2018</p>	Construction:	Injection	Terminal:	Open terminal	Material:	Open cable	Core:	2000	Size:	4000 (Height)	Mount:	ACB	Test frequency:	See technical file	Test range:	25-40	Country:	4800V - 100A
Construction:	Injection																		
Terminal:	Open terminal																		
Material:	Open cable																		
Core:	2000																		
Size:	4000 (Height)																		
Mount:	ACB																		
Test frequency:	See technical file																		
Test range:	25-40																		
Country:	4800V - 100A																		

Intertek																			
EC Type Examination Certificate																			
<b>CE</b>	<p><b>Issued to:</b> RUANG KONGSIKUN 59188-001 LTD SUNGU INDUSTRIAL ZONE, XINCHENG TOWN, RUANG DUTY, JIANGSU PROVINCE, CHINA</p> <p><b>Authorised Representative:</b> HANSEN STAR SAFETY PRODUCTS APAC (S) LTD 1-01 Village Square Tower, Jemena Centre, North Harbour City, Hong Kong</p> <p><b>Date of Issue:</b> 11 January 2018</p> <p><b>Expiry Date:</b> 11 February 2020</p> <p><b>Certificate No.:</b> L20170000047 (Extension of certificate L20170004196)</p> <p><b>Product Reference(s):</b> Safety Group: 4800V - 100A/2 4800V - 100A/4 4800V - 100A/6 4800V - 100A/8 4800V - 100A/10 4800V - 100A/12</p> <p><b>Description:</b>  <table border="0"> <tr> <td>Construction:</td> <td>Injection</td> </tr> <tr> <td>Terminal:</td> <td>Open terminal</td> </tr> <tr> <td>Material:</td> <td>Open cable</td> </tr> <tr> <td>Core:</td> <td>2000</td> </tr> <tr> <td>Size:</td> <td>4000 (Height)</td> </tr> <tr> <td>Mount:</td> <td>ACB</td> </tr> <tr> <td>Test frequency:</td> <td>See technical file</td> </tr> <tr> <td>Test range:</td> <td>25-40</td> </tr> <tr> <td>Country:</td> <td>4800V - 100A</td> </tr> </table> </p> <p><b>Signature:</b> <i>C.M.</i> <b>Date:</b> 11/01/2018</p> <p><b>Signature:</b> <i>[Signature]</i> <b>Date:</b> 11/01/2018</p> <p><b>Signature:</b> <i>[Signature]</i> <b>Date:</b> 11/01/2018</p> <p><b>Signature:</b> <i>[Signature]</i> <b>Date:</b> 11/01/2018</p>	Construction:	Injection	Terminal:	Open terminal	Material:	Open cable	Core:	2000	Size:	4000 (Height)	Mount:	ACB	Test frequency:	See technical file	Test range:	25-40	Country:	4800V - 100A
Construction:	Injection																		
Terminal:	Open terminal																		
Material:	Open cable																		
Core:	2000																		
Size:	4000 (Height)																		
Mount:	ACB																		
Test frequency:	See technical file																		
Test range:	25-40																		
Country:	4800V - 100A																		

# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection



# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY