Product Description

Product Name:	Keep warm fur lining winter rigger boots				
Item No:	W1023				
Upper and Sole:	Upper: Embossed split cow leather Sole: PU/ PU dual density sole				
Toe:	1. Steel toe cap to be impact resistant 200 Joules. To protect your feet toe without hazard.				
	2. non-steel toe is also provided.				
Midsole :	1. Steel plate to be puncture resistant 1100 Newton. To protect your feet without puncture by nail or sharp objects				
	2. non- steel plate is also provided				
Collar:	PU artificial leather				
Style:	No laces rigger boots with two loops				
Lining:	Keep warm fur lining				
Sockliner:	Soft wool felt insoles				
Construction:	PU injection				
Height:	27-28 cm (Average)				
Size:	37-47				
Standard:	CE EN ISO 20345:2011 S3 SRC or others.				
Guarantee:	6 months The sole is not broken from the middle or pulled off within six month after the goods getting to destination port. No guarantee for the upper.				
Package:	1 pair per color box, 10 pairs in a carton.				
Carton Size	68 x 65 x 34.5 cm				
Load quantity of Container:	1800pairs /1x20' container 3600pairs /1x40' container				

Product Pictures





SLIP-

RESISTANT



















COMPANY INFORMATION

TIGER MASTER

Tiger Master is safety shoes and <u>PVC rain boots</u> manufacturer. We have been qualified ISO 9001:2015 quality management system. Also, some of our hot sale models have qualified CE ENISO 20345:2011 and ASTM F2413-18. Meanwhile, we are also a professional brand for <u>PPE (Personal protective equipment)</u>, especially in the fields of safety gloves, working garments, helmets, safety vest, ear muff/plug, safety harness, rain coat/suit etc.

Thank you for your interest of Tiger Master, hope you can find the products you want and start our business cooperation. If you need more information, please do not hesitate to contact us, we are always ready here.







TIGER MASTER OFFICE SHOW





TIGER MASTER SAMPLE ROOM





SAFETY SHOES TEST





Toecap Test≥200 Joules



Midsole Test≥1200 Newtons



ESD Anti-Static Test



Tear Strength ≥120N



Bondness Test ≥4.0N/mm



Flex Tester ≥ 36,000T

Production Process



PERSONAL PROTECTIVE EQUIPMENT WORK SAFETY SOLUTION PROVIDER























