Product Description

Nome do Produto:	Abrasão resistente anti deslizamento de fibra de vidro de segurança
Item número:	TM1024.
Superior e sola:	KPU superior;PU + TPU sole,
Dedo do pé:	1. Tampa do pé de fibra de vidro para ser resistente ao impacto. Para proteger seus pés de pés sem perigo.
	2. Não é também fornecido.
Midsole:	1. As palmilhas anti-penetração não metálicas são resistentes à punção.Para proteger seus pés sem perfuração por unhas ou objetos afiados.
	2. Não é também fornecido
Colarinho:	Tecido de alta densidade
Língua:	Tecido de alta densidade
Resina:	Tecido de malha de ar suave para um ajuste de conforto
Calçados:	A palmilha ali-poli removível oferece suporte sob os pés superiores e conforto almofadado.
Construção:	Injeção moldada
Altura:	Corte baixo
Tamanho:	37-47.
Padrão:	CE EN ISO 20345: 2011 sb-p src ou outros.
Garantia:	6 meses A sola não é quebrada do meio ou retirada dentro de seis meses após as mercadorias chegando ao porto de destino.Nenhuma garantia para a parte superior.
Função:	Anti deslizamento, óleo / ácido / gasolina / químico / impacto / perfuração / resistente à abrasão, metal livre, leve, absorção de choque.
Pacote:	1 par por caixa de cor, 10 pares por caixa. Tamanho da caixa:58.5.X.40.X.32.5.cm
Quantidade de carga de contêiner:	3300Pairs / 1x20 'contêiner 6600Pairs / 1x40 'contêiner

Product Pictures

EU TYPE EXAMINATION CERTIFICATE

intertek

CE

APPROVED BODY DIN2

Issued to: HEILONGJIANG SAFER CO., LTD.
BAIKAI PLAZA PLAZA, NO.201 DAJIANGNAN ROAD, HARBIN, CHINA

Issue Date: 15 September 2009

Expiry Date: 15 September 2019

Certificate No.: 01120080111 (Extension to Certificate LE0700371001)

Product Reference(s): BF6378 (HI-XIAN)
BF6201 (HI-XIAN-1)

Description:
Construction : INJECTION
Toecap : Composite Toecap
BF6201 : Non-metallic anti-puncture insole board
Lace : 1338
Sole : 1338 PU/PA
Mould : 1338
Test Report(s) : SGS 1407HO0114-1
Size Range : 39-46
Category : II A BK

Issued at: CBall Date: 15/09/2009

Certification Manager: Date: 15/09/2009

For and on behalf of TÜV Testing Services (UK) Limited

EWC

Certificate of Quality Management System

Certificate No.: 105821Q

Certified that

HEILONGJIANG SAFER CO., LTD.

Has established a Quality Management System which is in Accordance with the Requirements of the Standard (Not Applicable to Clause 8.3)

GB/T 19001-2016/ISO 9001:2015

SCOPE OF CERTIFICATION

Sales of Personal Protective Equipments (Foot Protective, Hand Protective, Head Protective and Body Protective) and Traffic Safety Products (Safety Net, Road Cone, Safety Barrel, Speed Bump, Warning Belt, Caution Light, Triangle Sign, Batons, Reflecting Mirror, Reflector, Reflective Corner Guard and Reflecting Spike)

Validity of Certification: Nov. 17, 2021 To: Nov. 16, 2024
Issue Date: Nov. 17, 2021

(The effectiveness of this Certificate shall be validated by periodic surveillance audit of EWC for maintenance. Conditions on effectiveness of certificate see http://www.cnca.gov.cn and official website of Certification and Accreditation Administration of People's Republic of China http://www.cnca.gov.cn)

Expiry of This Certificate is Nov. 2022
Serial No.: V1007072

EWC:

ANAB IAF

EU TYPE EXAMINATION CERTIFICATE

intertek

CE

APPROVED BODY DIN2

Issued to: HARBIN HAI SAFETY PRODUCTS MFG. CO., LTD.
LINN VILLAGE, XINHUA TOWN, ACHENG DISTRICT, HARBIN, HEILONGJIANG PROVINCE, CHINA

Issue Date: 06 September 2019

Expiry Date: 06 September 2024

Certificate No.: LE0700371001

Product Reference(s): BM (FW-01)
SAFETY BOOTS

Description:
Construction : INJECTION
Toecap : ASTM STEEL TOECAP
Midsole : CRW-GBE STEEL PLATE
Last : HA-BBB
Sole : PVC & NITRILE
Mould : HA-A
Test Report(s) : GZHTR0904073, GZHTR0904194
Size Range : EU36-EU47
Category : II A BK

Issued at: Date:

Certification Manager: Date:

For and on behalf of TÜV Testing Services (UK) Limited

[PRODUCTION PROCESS]

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY