

Product Description

Nome do Produto:	S3 SRC Alta Rigger Botas
Item número:	TM5009.
Superior e sola:	Superior: Couro de vaca dividido em relevo SOLE: PU / PU densidade de densidade
Dedo do pé:	1. Tampa de dedo do pé para ser resistente a impacto 200 joules. 2. Toe não-aço também é fornecido.
Midsole:	1. Placa de aço a ser resistente à punção 1100 Newton. 2. Placa não de aço também é fornecida
Collar & Lingüna:	Sem colarinho
estilo:	Nenhuma botas de solda de renda
Resina:	Tecido de malha de ar (será mantido seus pés confortáveis)
Sockliner:	Anti estático moldado EVA revestido com tecido de malha de ar ou outros como suas necessidades (reduza bastante os pés dor e fadiga do trabalho diário)
Construção:	Injeção do PU.
Altura:	29-30 cm
Tamanho:	38-47.
Padrão:	CE EN ISO 20345: 2011 S3P SRC
Garantia:	6 meses
Pacote:	Embalagem de caixa interna de cor, 10 pares em uma caixa.
Tamanho da caixa	68 x 65 x 34,5 cm
Quantidade de carga de contêiner:	1800Pairs / 1x20 'contêiner 3600Pairs / 1x40 'contêiner

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T